



American Pneumatic Tools

MODEL 260 SERIES CHIPPING HAMMERS



The APT Chipping Hammers are used for work such as scaling, chiseling, removing concrete build-up from the inside of concrete mixers, light concrete demolition, cement finishing and form stripping.

FEATURES

- New patented Ball Valve design (Pat. # 8,276,682 B2) - more forgiving of dirt and debris, easier to maintain, made from corrosion resistant material
- Ball-type throttle valve - less complicated, makes teasing the throttle easier
- Drop forged steel handle and collar
- Deep case hardened alloy steel cylinder
- Replaceable nose bushing
- 2 - bolt design for easier field maintenance
- Adjustable exhaust deflector
- Available in 3" and 4" strokes
- Tools come standard with:
Standard oval collar retainer (Part # 7022)
Locking Spring (Part # 1941)
6 ft Whip hose assembly (Part # 18832)
- Optional quick change retainer systems available are:
5550 Ball - type Retainer with Locking Spring
18290 Ball - type, Bolt-on Retainer

SPECIFICATIONS

Part #	18667	18670	18668	18671
Nose Bushing	.680 Round	.580 Hex	.680 Round	.580 Hex
Bore Diameter(inches)	1-1/8"		1-1/8"	
Stroke (inches)	3"		4"	
Blows per Minute	1650		1375	
CFM @ 90 psi	33 - 35		34 - 36	
Weight (lbs)	14		15	
Length (inches)	14-9/16"		15-9/16"	
Air Inlet Size	7/8-24 - FEMALE			

For assistance in any sales, technical, maintenance or repair questions, please call APT @
Phone: (800) 532-7402 or (714) 285-2828 • Fax: (800) 715-6502 or (714) 285-2829
1000 S. Grand Ave, Santa Ana, CA 92705



American Pneumatic Tools

MODEL 650 SERIES CHIPPING HAMMERS



The APT Chipping Hammers are used for work such as scaling, chiseling, removing concrete build-up from the inside of concrete mixers, light concrete demolition, cement finishing and form stripping.

FEATURES

- Flapper valve design allows dirt to pass without stopping the tool
- Traditional pistol grip handle made from drop forged steel
- Deep case hardened alloy steel cylinder
- Replaceable nose bushing
- Adjustable exhaust deflector
- Available in 2", 3" and 4" strokes
- Tools come standard with:
Standard oval collar retainer (Part # 7022)
Locking Spring (Part # 1941)
6 ft Whip hose assembly (Part # 18832)
- Optional quick change retainer systems available are:
5550 Ball-type Retainer with lock spring
18290 Bolt-on type

SPECIFICATIONS

Part #	5298	5299	5300	5301	5302	5303
Nose Bushing	.680 Round	.580 Hex	.680 Round	.580 Hex	.680 Round	.580 Hex
Bore Diameter (inches)	1-1/8"		1-1/8"		1-1/8"	
Stroke (inches)	2"		3"		4"	
Blows per Minute	2100		1650		1375	
CFM @ 90 psi	32 - 34		33 - 35		34 - 36	
Weight (lbs)	12		14		16	
Length (inches)	13-1/4"		15-1/4"		16"	
Air Inlet Size	7/8-24 - FEMALE					

For assistance in any sales, technical, maintenance or repair questions, please call APT @
Phone: (800) 532-7402 or (714) 285-2828 • Fax: (800) 715-6502 or (714) 285-2829
1000 S. Grand Ave, Santa Ana, CA 92705

Website: www.apr-tools.com • e-mail: info@apr-tools.com

TDS-1060 Rev C

© 2017 AMERICAN PNEUMATIC TOOLS a business unit within: Construction Equipment North America LLC.



American Pneumatic Tools

MODEL M43/M44 SERIES 4 BOLT CHIPPING HAMMERS



Features

- APT patented ball valve (US patent #8,276,682 B2)
- New drop forged handle, fitted with four grade 8 bolts for ease of maintenance
- Deep case hardened alloy steel cylinder for high wear resistance
- Adjustable exhaust deflector
- Available in 3" and 4" strokes
- Built-in air inlet screen
- 3 styles of retainer systems (oval collar standard)
- Steel braid reinforced whip hose assembly included (7/8-24 male swivel and universal coupler)
- Available in .680 round or .580 hex bushing styles

APT chipping hammers are used for scaling, chiseling, removing concrete build up from the inside of concrete mixers, form stripping, etc

Specifications	Model M43R	Model M43H	Model M44R	Model M44H
APT Part #	18850	18851	18852	18853
Nose Bushing	1-1/8	1-1/8	1-1/8	1-1/8
Stroke (in)	3	3	4	4
Blows per minute	1650	1650	1375	1375
CFM @90 psi	33 – 35	33 – 35	34 – 36	34 – 36
Weight (lb)	21	21	22	22
Length (in)*	16-3/4	16-3/4	17-3/4	17-3/4
Air Inlet Size	7/8-24 female	7/8-24 female	7/8-24 female	7/8-24 female

*excluding retainer

For assistance in any sales, technical, maintenance or repair questions, please call APT @
 Phone: (800) 532-7402 or (714) 285-2828 • Fax: (800) 715-6502 or (714) 285-2829
 1000 S. Grand Ave, Santa Ana, CA 92705

Website: www.apr-tools.com • e-mail: info@apr-tools.com

TDS-1171 Rev A

© 2017 AMERICAN PNEUMATIC TOOLS a business unit within: Construction Equipment North America LLC.