

APT Portable Generators



**PROVEN POWER.
RUGGED RELIABILITY.**

www.apr-tools.com | 800.532.7402

APT Portable Generators

Applying insights gained from industrial customers, rental companies, public utilities, and other end users, APT generators are designed to withstand the most demanding on-site conditions and environments.

Built to last, an APT generator will provide years of dependable service for your electrical power generation needs.

Features

- Sound-attenuated, rugged steel enclosure
- Large doors and access for superior serviceability
- Single point lifting beam
- Trailer or skid configurations available
- Digital controllers with multiple protections built-in; including low fuel warning



	APTG 25	APTG 45	APTG 70	APTG 95	APTG 125
Rated Prime Power 3Ø (kW/kVA)	20 / 25	36 / 45	56 / 70	76 / 95	100 / 125
Voltage Selection 3Ø	208 / 240 / 480	208 / 240 / 480	208 / 240 / 480	208 / 240 / 480	208 / 240 / 480
Amperage @ 208 / 240 / 480V 3Ø	61 / 60 / 30	125 / 108 / 54	168 / 168 / 84	264 / 229 / 114	300 / 300 / 150
Rated Prime Power 1Ø (kW/kVA)	16/16	27 / 27	43 / 43	55 / 55	76 / 76
Voltage Selection 1Ø	120 / 240	120 / 240	120 / 240	120 / 240	120 / 240
Amperage @ 120 / 240V 1Ø	2 x 67 / 67	2 x 90 / 90	2 x 180 / 180	2 x 228 / 228	2 x 271 / 271
Sound Pressure Level @ 23' (7m) @ 75% Load - dB(A)	67	66	69	69	69
Receptacles*	2 @ 20A - 125V GFCI duplex; 2 @ 50A - 125/250V Twist-Lock				
Alternator Make	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer
Model	LSA40M5	LSA42.3 S5	LSA43.2L9	LSA44.3 S3	LSA43.3 S5
Degree of Protection / Insulation Class	IP23/H	IP23/H	IP23/H	IP23/H	IP23/H
Excitation	AREP	AREP	AREP	AREP	AREP
Engine Make	Isuzu	Isuzu	Isuzu	John Deere	John Deere
Model	4LE2T	4LE2X	4JJ1X	4045HFG04	4045HFG06
Displacement - L	2.18	2.18	2.99	4.5	4.5
Cylinders	4	4	4	4	4
EPA Tier	T4F	T4F	T4F	T4F	T4F
Gross Engine Power Output - HP	40	66	96	133	172
Rated Speed - rpm	1,800	1,800	1,800	1,800	1,800
Engine Speed Control	Electronic	Electronic	Electronic	Electronic	Electronic
Fuel Tank Capacity - gal. (L)	72.5 (274)	72.5 (274)	110 (416)	168 (628)	168 (628)
Fuel Consumption, GPH (LPH) @ 75% Load	1.4 (5.5)	2.15 (8.1)	2.9 (10.9)	4.0 (15.4)	5.25 (19.9)
Run Time @ 75% Load, 90% Fuel Capacity - Hours	46	30	34	38	29
Dimensions, Genset w/Trailer (L x W x H) - in.	121.5 x 57 x 75.5	121.5 x 57 x 75.5	136 x 65 x 75	162 x 68 x 86	162 x 68 x 86
Weight, Trailer Mounted (Wet) - lbs.	2,396	2,625	3,690	6,485	6,485
Dimensions, Skid Mount (L x W x H) - in.	75 x 34 x 54.5	75 x 34 x 54.5	94 x 41 x 64	108 x 43 x 76	108 x 43 x 76
Weight, Skid Mount (Wet) - lbs.	2,290	2,440	3,100	6,485	6,485

*GFCI outlets may have higher than 120VAC in certain settings

AMERICAN PNEUMATIC TOOLS

1000 S. Grand Ave.
Santa Ana, CA 92705

Tel 714.285.2828 | Fax 714.285.2829
Toll Free Tel 800.532.7402 | Fax 800.715.6502

BUILT TO LAST SINCE 1938

www.apr-tools.com
info@apr-tools.com

